



FS 74 Z

FS 74z.1




2400	1800	1410	1160	kg
3,00	4,00	5,00	5,90	m
5290	3970	3110	2560	lbs
9'10"	13'1"	16'5"	19'4"	ft

FS 74z.2



2300	1720	1320	1070	880	kg
3,00	4,00	5,00	6,00	7,00	m
5070	3790	2910	2360	1940	lbs
9'10"	13'1"	16'5"	19'8"	22'12"	ft

FS 74z.2P



2150	1450	1140	930	760	650	590	kg
3,00	4,00	5,00	6,00	7,00	8,00	8,85	m
4740	3200	2510	2050	1680	1430	1300	lbs
9'10"	13'1"	16'5"	19'8"	22'12"	26'3"	29'0"	ft

Standard features

- control
- structure



optional features

- control



*E.C. market specific equipment



	kN.m-lbs	bar-psi	l/min- gal min	kg-lbs	°	mm-ft/inc	mm-ft/inc	mm-ft/inc	mm-ft/inc
FS 74 Z.1	71-52366	220-3190	50-13	1410-3102	400	2270-7'5"	980-3'3"	2600-8'6"	4100-13'5"
FS 74 Z.2	68-50154	220-3190	50-13	1490-3278	400	2270-7'5"	980-3'3"	2600-8'6"	4100-13'5"
FS 74 Z.2P	63-46466	220-3190	50-13	1690-3730	400	2480-8'2"	1010-3'4"	2360-7'9"	4100-13'5"