



Safety Data Sheet

Nr.: 980.1096

Lubricant for mini grease gun, 110 g

Ver.1.0

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

1.1 Produktidentifikator

Product Name: Lubricant for mini grease gun, 110 g

Product Code: 980.1096

1.2 Details of the supplier providing the safety data sheet

KS Tools

Werkzeuge und Maschinen GmbH

Seligenstädter Grund 10–12

63150 Heusenstamm - GERMANY

customerservice@kstools.com

www.kstools.com

1.3 Emergency number, telephone number: POISON CONTROL/TRANSPORT EMERGENCY -

Deutschland, Österreich, Schweiz, Luxemburg (24h)

Tel: +49 89 220 61012 / 0800 000 7801 (Deutsch, Englisch)

Numéro d'appel d'urgence en cas d'intoxication/d'accident -

Suisse, Luxembourg (24h): Tel: ++33 1 7211 0003 (Français)

NOTRUF: 112

Emergency number:

EMERGENCY CONTACT – UK, UAE,

South Africa (24h): Tel: ++441865407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE,

South Africa (24h): Tel: ++44 1865 407333 (English)

2. HAZARDS IDENTIFICATION

NFPA Ratings (Scale 0-4): Health=1 Fire=1 Reactivity=0

The Most Important Hazardous Effects:

1. Adverse Human Health Effects:

(For Long Term Exposure)

- Inhalation : no information on significant adverse effects.
- Skin Contact : skin disorders.
- Eye Contact : irritation.
- Ingestion : no information is available.

2. Environmental Effects: no information is available.

Methods for Cleaning Up:

1. Clean up small spills using sand or other non-combustible material.
2. Collect spilled material in appropriate container for disposal.
3. Where feasible and appropriate, remove contaminated soil.
4. Follow prescribed procedures for reporting and responding to larger releases.

7. HANDLING AND STORAGE

Handling:

1. Wear protective equipment, if exposure conditions warrant.
2. Wash thoroughly after handling.
3. Use with adequate ventilation.
4. Handle in accordance with all current regulations and standards.

Storage:

1. Keep away from heat, sparks and flames.
2. Store in well-ventilated area.
3. Store in a tightly closed container.
4. Store in a cool, dry place.
5. Bond and ground during transfer.
6. Keep separated from incompatible substances.
7. Storage in accordance with all current regulations and standards.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Control:

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Control Parameter:

HAZARDOUS MATERIAL	TWA	STEL	CEILING
Mineral Oil Mist	ACGIH: 5 mg/m ³ NIOSH: 5 mg/m ³ OSHA : 5 mg/m ³	NIOSH : 10mg/m ³ UK OES : 10mg/m ³	–

